

NEW

# RÉVO

ELECTROMECHANICAL GEAR MOTOR WITH ARTICULATED ARM FOR SWING GATES  
WITH LEAVES UP TO 2,3 m, 24 Vdc



## PLUS



RÉVO combines a lighting system with an articulated arm gear motor. Designed for swing gates made of PVC or wooden leaves

Ideal for narrow columns or pillars with reduced dimensions. Compact shape and silent movement, made of strong die-casting aluminium and UV resistant covers

The articulated arm allows the installation of RÉVO in all those difficult situations where there is a significant depth between the leaf and the column, or with very narrow columns (10x10 cm). Available in two versions, with articulated arm or sliding arm for pedestrian gates

The unlocking system is simple and intuitive. The unlock is possible also using the transmitter Sub. Unlock from the outside is optional

The installation of the motor is also eased by the front and rear brackets located at the same level

Back-up battery (optional) on board

Double mechanical built-in stop



Stylish design screwless at sight



Possibility to unlock motor with transmitter



Compact dimensions (width 12 cm)




Aluminium arm with metal pin

## MODELS


CODE	DESCRIPTION	PCS PALLET
REVO2024	For swing gates with maximum length 2,3 m or weight 250 kg, 24 Vdc motor (1 pc)	16
REVO2024S	For swing gates with maximum length 2,3 m or weight 250 kg, 24 Vdc motor. Without control unit (1 pc)	16

TECHNICAL DATA	REVO2024	REVO2024S
<b>MECHANICAL DATA</b>		
torque	Nm	120
working cycle	%	80
opening time at 90°	sec	adjustable
<b>ELECTRICAL DATA</b>		
control board	14A	-
power	Vac (Vdc)	230 (24)
motor consumption	A	0,6
absorbed power	W	140
integrated lights	yes	yes
<b>GENERIC DATA</b>		
protection degree	IP	44
dimensions (L - P - H)	mm	120 - 250 - 350
weight	kg cad	10,5
working temperature	°C	-20 + 55
leaves maximum weight	Kg	250

### LIMIT USE



Gate shape and height and weather conditions can considerably reduce the values shown above, in the graph. 230 Vac motors are suggested for windy areas




A min	100
C max	200
D min	450

## ACCESSORIES



**EL5-C**  
Horizontal 12 V electrolock

PC 1



**KBP**  
Battery back-up kit for 14A control unit

PC 1



**999LED**  
Pair of led lights cold white (for 24 Vdc)

PCS 2



**KC**  
Unlock key cilinder

PC 1



**REV1**  
Slide arm

PC 1



**REV2**  
Pedestrian gate arm

PC 1



**REV3**  
External release unlock kit

PC 1



**BMET**  
Metal box with release system

PC 1



**TS**  
Warning board

PC 1